

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Blok PTV 6
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
Rated heat output	Prated	6	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	P_4	5,8	kW
Auxiliary electricity consumption			
At full load	el_{max}	5,876	kW
In standby mode	P_{SB}	0,006	kW
Declared load profile			
Daily electricity consumption	Q_{elec}		kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	η_4	38,7	%
Other items			
Standby heat loss	P_{stby}	0,084	kW
Water heating energy efficiency	η_{wh}		%
Daily fuel consumption	Q_{fuel}		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(**) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Blok PTV 9
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
Rated heat output	Prated	9	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	P_4	8,7	kW
Auxiliary electricity consumption			
At full load	el_{max}	8,786	kW
In standby mode	P_{SB}	0,006	kW
Declared load profile			
Daily electricity consumption	Q_{elec}		kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	η_4	38,7	%
Other items			
Standby heat loss	P_{stby}	0,084	kW
Water heating energy efficiency	η_{wh}		%
Daily fuel consumption	Q_{fuel}		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(**) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Blok PTV 12
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
Rated heat output	Prated	12	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	P_4	11,6	kW
Auxiliary electricity consumption			
At full load	el_{max}	11,696	kW
In standby mode	P_{SB}	0,006	kW
Declared load profile			
Daily electricity consumption	Q_{elec}		kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	η_4	38,7	%
Other items			
Standby heat loss	P_{stby}	0,084	kW
Water heating energy efficiency	η_{wh}		%
Daily fuel consumption	Q_{fuel}		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(**) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Blok PTV 15
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
Rated heat output	Prated	15	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	P_4	14,6	kW
Auxiliary electricity consumption			
At full load	el_{max}	14,606	kW
In standby mode	P_{SB}	0,006	kW
Declared load profile			
Daily electricity consumption	Q_{elec}		kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	η_4	38,9	%
Other items			
Standby heat loss	P_{stby}	0,084	kW
Water heating energy efficiency	η_{wh}		%
Daily fuel consumption	Q_{fuel}		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(**) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Blok PTV 18
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
Rated heat output	Prated	18	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	P_4	17,5	kW
Auxiliary electricity consumption			
At full load	el_{max}	17,516	kW
In standby mode	P_{SB}	0,006	kW
Declared load profile			
Daily electricity consumption	Q_{elec}		kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	η_4	38,9	%
Other items			
Standby heat loss	P_{stby}	0,084	kW
Water heating energy efficiency	η_{wh}		%
Daily fuel consumption	Q_{fuel}		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(**) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Blok PTV 20
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
Rated heat output	Prated	19	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	P_4	19,4	kW
Auxiliary electricity consumption			
At full load	el_{max}	19,456	kW
In standby mode	P_{SB}	0,006	kW
Declared load profile			
Daily electricity consumption	Q_{elec}		kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	η_4	38,8	%
Other items			
Standby heat loss	P_{stby}	0,084	kW
Water heating energy efficiency	η_{wh}		%
Daily fuel consumption	Q_{fuel}		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(**) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Blok PTV 22
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
Rated heat output	Prated	21	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	P_4	21,3	kW
Auxiliary electricity consumption			
At full load	el_{max}	21,396	kW
In standby mode	P_{SB}	0,006	kW
Declared load profile			
Daily electricity consumption	Q_{elec}		kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	η_4	38,7	%
Other items			
Standby heat loss	P_{stby}	0,084	kW
Water heating energy efficiency	η_{wh}		%
Daily fuel consumption	Q_{fuel}		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(**) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Blok PTV 24
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
Rated heat output	Prated	23	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	P_4	23,3	kW
Auxiliary electricity consumption			
At full load	el_{max}	23,361	kW
In standby mode	P_{SB}	0,006	kW
Declared load profile			
Daily electricity consumption	Q_{elec}		kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	η_4	38,8	%
Other items			
Standby heat loss	P_{stby}	0,084	kW
Water heating energy efficiency	η_{wh}		%
Daily fuel consumption	Q_{fuel}		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(**) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Blok PTV 28
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
Rated heat output	Prated	27	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	P_4	27,2	kW
Auxiliary electricity consumption			
At full load	el_{max}	27,241	kW
In standby mode	P_{SB}	0,006	kW
Declared load profile			
Daily electricity consumption	Q_{elec}		kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	η_4	38,9	%
Other items			
Standby heat loss	P_{stby}	0,100	kW
Water heating energy efficiency	η_{wh}		%
Daily fuel consumption	Q_{fuel}		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(**) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Blok PTV 32
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
Rated heat output	Prated	31	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	P_4	31,0	kW
Auxiliary electricity consumption			
At full load	el_{max}	31,121	kW
In standby mode	P_{SB}	0,006	kW
Declared load profile			
Daily electricity consumption	Q_{elec}		kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	η_4	38,8	%
Other items			
Standby heat loss	P_{stby}	0,100	kW
Water heating energy efficiency	η_{wh}		%
Daily fuel consumption	Q_{fuel}		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(**) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Blok PTV 36
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
Rated heat output	Prated	35	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	P_4	34,9	kW
Auxiliary electricity consumption			
At full load	el_{max}	35,001	kW
In standby mode	P_{SB}	0,006	kW
Declared load profile			
Daily electricity consumption	Q_{elec}		kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	η_4	38,8	%
Other items			
Standby heat loss	P_{stby}	0,100	kW
Water heating energy efficiency	η_{wh}		%
Daily fuel consumption	Q_{fuel}		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(**) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Blok PTV 40
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
Rated heat output	Prated	39	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	P_4	38,8	kW
Auxiliary electricity consumption			
At full load	el_{max}	38,881	kW
In standby mode	P_{SB}	0,006	kW
Declared load profile			
Daily electricity consumption	Q_{elec}		kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	η_4	38,8	%
Other items			
Standby heat loss	P_{stby}	0,100	kW
Water heating energy efficiency	η_{wh}		%
Daily fuel consumption	Q_{fuel}		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(**) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).